

PHIMO ULTRA PLUS 0W20

Description:

A modern, synthetic, fuel economy motor oil based on special selected synthetic base oils with a high viscosity index and a well balanced choice of advanced additives to obtain the following properties:

- a lower fuel consumption
- a high and very stable viscosity index
- a high resistance against shearing
- a fast cold start
- a very strong resistance against oxidation
- a safe lubrication film at very high temperatures
- a very good detergency and dispersion
- a very strong protection against wear, corrosion and foaming

Application:

A fuel economy, special composed synthetic motor oil recommended for use in petrol engines of passenger cars. This oil is fully backward compatible with GM dexos1 Gen 2. This oil is also suitable for the PATAC requirements of China 6 emission norms.

Specifications:

API SP Resource Conserving
ILSAC GF-6A
Meets the requirements of:
GM dexos 1 Gen 3
Chrysler MS 6395
Fiat 9.55535-CR1
Ford WSS-M2C947-A/B1 / WSS-M2C962-A1
GM 6094M

Typicals

Density at 15 °C, kg/l	0,844
Viscosity -35 °C, mPa.s	5740
Viscosity 40 °C, mm²/s	44,50
Viscosity 100 °C, mm²/s	8,40
Viscosity Index	168
Flash Point COC, °C	226
Pour Point, °C	-42
Total Base Number, mgKOH/g	7,4
Sulphate Ash, %	0,78