

PHIMO ULTRA PLUS 5W30

Description:

Universal, synthetic fuel economy motor oil developed according the most recent technology and based on specially selected synthetic base oils with a high natural viscosity index. With the addition of a well-balanced choice of advanced additives the following properties are obtained:

- a lower fuel consumption
- a high and very stable viscosity index
- a high resistance against shearing
- a fast cold start
- a safe lubrication film at very high temperatures
- reduced formation of combustion ashes
- a very good detergency and dispersion
- a very strong protection against wear, corrosion and foaming

Application:

This universal synthetic motor oil is suitable for use in petrol and diesel engines, with or without turbo-charging. Moreover this lubricant is also very suitable for passenger car diesel engines with pump-injector-unit. This product meets the requirements of several OEM's and thus has a wide application.

Specifications:

Performance level:
ACEA C3
API SN, API SN Plus
BMW Longlife-04
GM dexos 2
MB 229.31/229.51/229.52
Opel OV0401547
VW 505.00/505.01

Typicals:

Density at 15 °C, kg/l	0,856
Viscosity -30 °C, mPa.s	5470
Viscosity 40 °C, mm ² /s	69,50
Viscosity 100 °C, mm ² /s	12,10
Viscosity Index	174
Flash Point COC, °C	210
Pour Point, °C	-36
Total Base Number, mgKOH/g	7,3
Sulphate Ash, %	0,75