

PHIMO ULTRA PLUS 5W40

Description:

A very modern, synthetic, universal motor oil based on special selected synthetic base oils with a high viscosity index and a well balanced choice of advanced additives to obtain the following properties:

- a high and very stable viscosity index
- a high resistance against shearing
- a fast cold start
- a very strong resistance against oxidation
- a safe lubrication film at very high temperatures
- a very good detergency and dispersion
- a very strong protection against wear, corrosion and foaming

Application:

A universal, special composed synthetic motor oil recommended for use in petrol and diesel engines, with or without turbo-charging, in passenger cars and delivery vans for which the most modern specifications are required.

Specifications:

ACEA A3/B4
API SP/CF
Meets the requirements of:
BMW Longlife-01
MB 229.5 / 229.3 / 226.5
Opel GM-LL-B-025
Porsche A40
PSA B71 2296
Renault RN0700 / RN0710
VW 502.00 / 505.00 / 501.01

Typicals

Density at 15 °C, kg/l	0,857
Viscosity -30 °C, mPa.s	6260
Viscosity 40 °C, mm²/s	91,00
Viscosity 100 °C, mm²/s	15,00
Viscosity Index	174
Flash Point COC, °C	234
Pour Point, °C	-39
Total Base Number, mgKOH/g	10,8
Sulphate Ash, %	1,32